

C229 PERF-TAPE

DESCRIPTION

THIS TRANSPARENT POLYPROPYLENE FILM IS COATED WITH A CLEAR ACRYLIC ADHESIVE AND IS CUSTOM SLIT WITH A PERFORATION DOWN THE CENTER OF THE ROLL. THIS CONTINUOUS PERFORATION IS IN THE MACHINE DIRECTION, WHICH ALLOWS FOR THE TAPE TO BEND WITH THE PERFORATION OR FANFOLD SPLICE.

THIS PRODUCT IS SPECIFICALLY DESIGNED FOR SPLICING FOR ALL CONTINUOUS FORMS OR PERFORATED LABELS. IT IS APPLIED AS A SPLICE BETWEEN THE TWO FORMS AND THE PERFORATION ALLOWS FOR EASY SEPARATION.

AVAILABLE SIZES

1/4" x 72 yards	144 Rolls/Case
5/16" x 72 yards	108 Rolls/Case
3/8" x 72 yards	96 Rolls/Case
1/2" x 72 yards	72 Rolls/Case
1" x 72 yards	36 Rolls/Case

PRODUCT SPECIFICATIONS

BACKING:	POLYPROPYLENE
THICKNESS:	2 MIL
ADHESIVE:	ACRYLIC
TENSILE:	15 LBS./IN.
ADHESION:	18 OZ/IN
ELONGATION:	120%
TEMPERATURE:	32° to 160°F

Conversource delivers these and other fine products for your everyday applications and most challenging print jobs.

DATA SHEET



Premier Service
Industrial Products Distributor



Daetwyler



ALPHASONICS
ULTRASONIC CLEANING SYSTEMS



CONVERSOURCE INC
1510 PAGE INDUSTRIAL BLVD.
SAINT LOUIS, MISSOURI 63132 USA

PHONE: (800) 808-1565
FAX: (800) 482-7688

WWW.CONVERSOURCE.COM
INTEGRATEDSOLUTIONS@CONVERSOURCE.COM